

# Warystory typu JVR-10N

## SPECIFICATION

Part No	Maximum allowable Voltage		Maximum Energy		Withstanding Surge Current		Rated Wattage (W)	Varistor Voltage V1mA (V)	Maximum Clamping Voltage V5A (V)	Typical Capacitance (reference) @1KHz (pF)
	ACrms (V)	DC (V)	(10/1000us) (J)	(2ms) (J)	1 time (A)	2 times (A)				
WA 10N0680k	420	560	102.2	73.0	2500	1250	0.4	680(612-748)	1120	150
WA 10N0620k	385	505	102.2	73.0				620(558-682)	1025	160
WA 10N0560k	350	460	99.4	71.0				560(504-616)	920	180
WA 10N0510k	320	415	99.4	71.0				510(459-561)	845	200
WA 10N0470k	300	385	99.4	71.0				470(423-517)	775	210
WA 10N0430k	275	350	88.2	63.0				430(387-473)	710	230
WA 10N0390k	250	320	81.2	58.0				390(351-429)	650	260
WA 10N0360k	230	300	74.2	53.0				360(324-396)	595	280
WA 10N0330k	210	275	68.6	49.0				330(297-363)	550	300
WA 10N0300k	190	250	63.0	45.0				300(270-330)	500	330
WA 10N0270k	175	225	57.4	41.0				270(243-297)	455	370
WA 10N0240k	150	200	50.4	36.0				240(216-264)	395	420
WA 10N0220k	140	180	46.2	33.0				220(198-242)	360	450
WA 10N0200k	130	170	42.0	30.0				200(185-225)	340	500
WA 10N0180k	115	150	30.8	22.0	180(162-198)	300	560			
WA 10N0150k	95	125	25.2	18.0	150(135-165)	250	670			
WA 10N0120k	75	100	21.0	15.0	120(108-132)	200	830			
WA 10N0100k	60	85	18.2	13.0	100(90-110)	165	1000			
WA 10N0082k	50	65	16.8	12.0	82(74-90)	135	1200			
WA 10N0068k	40	56	15.4	11.0	68(61-75)	#135	1500			
WA 10N0056k	35	45	12.9	9.2	56(50-62)	#110	1800			
WA 10N0047k	30	38	10.8	7.7	47(42-52)	#93	2100			
WA 10N0039k	25	31	9.1	6.5	39(35-43)	#77	2600			
WA 10N0033k	20	26	7.4	5.3	33(30-36)	#65	3000			
WA 10N0027k	17	22	6.0	4.3	27(24-30)	#53	3700			
WA 10N0022k	14	18	4.5	3.2	22(18.7-26)	#43	4500			
WA 10N0018l	11	14	2.8	2.0	18(14.4-21.6)	#36	5600			

## DIMENSIONS

DIMENSIONS(mm)	Model No.	T MAX.	D MAX.	H MAX.	d.	E±0.8	L MIN.
	WA 10N0018L	4.6	14	17	0.8	7.5	20
	WA 10N0068k	5.3					
	WA 10N0082	4.5	14	17	0.8	7.5	20
	WA 10N0470k	6.5					
	WA 10N0510k	6.5	14	19	0.8	7.5	20
	WA 10N0820	9.7					