



Specifications

Current Rating: 2Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 500V AC/DC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

Materials

Contact Material: Brass

**Insulation Material: Polyester, UL94V-0, Nylon 6T

**Max solder temperature: 260 C for 10 sec

ROHS COMPLIANT

Ordering Information

BXHLSV1 - XX XX XXX X B
 No. of Pins-Standard Plating Per Row 04-25
 01=Gold Flash 02=Gold 3U"
 11=Tin
 XX=Select Plating
 Pin Length 001=W/7.70
 XXX=Select W T=NL6T(Standard)
 Material L=LCP B=Brass

GENERAL TOLERANCE	ANGLE TOLERANCE	DESIGN	DATE	ELEETE TECHNOLOGY CO., LTD 德徠得股份有限公司	FILE NAME (品名)	PART NO (料号)	DRAWING NO.(图号)	REV/A0
X ±0.38 .XX ±0.25 .XXX ±0.13	X° ±5' .XX° ±12' .XXX° ±0.5°	Andy2005.08.12						
UNIT:mm	SCALE 1:1	CHECK	DATE					
A4		APPRO.	DATE					
		SHEET: 1 of 1						